



L890-__AU Infrared LED Lamp

This series of L890-__AU is a GaAlAs LED mounted on a lead frame and encapsulated in various types of epoxy lens which offer different design settings. On forward bias, it emits a high power radiation of typical 15W with a peak wavelength at 880nm.

1) Specifications

- | | |
|---------------------|-------------------|
| (1) Chip material | AlGaAs |
| (2) Peak wavelength | 880nm |
| (3) Package | Clear epoxy resin |
| (4) Lead frame | Soldered |

2) Absolute Maximum Ratings

Item	Symbol	Maximum Rated Value	Unit	Ambient Temperature
Power Dissipation	P _D	150	mW	T _a =25°C
Forward Current	I _F	100	mA	T _a =25°C
Pulse Forward Current	I _{FP}	500	mA	T _a =25°C
Reverse Voltage	V _R	5	V	T _a =25°C
Operating Temperature	T _{OPR}	-30 ~ +85	°C	T _a =25°C
Storage Temperature	T _{STG}	-30 ~ +100	°C	
Soldering Temperature	T _{SOL}	260	°C	

3) Electro-Optical Characteristics [T_a=25°C]

Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	V _F	I _F =50mA		1.45	1.70	V
Reverse Current	I _R	V _R =5V			10	uA
Total Radiated Power	P _O	I _F =50mA	10.0	15.0		mW
Peak Wavelength	λ _P	I _F =50mA		880		nm
Half Width	Δλ	I _F =50mA		75		nm
Rise Time	t _r	I _F =50mA		800		ns
Fall Time	t _f	I _F =50mA		400		ns

4) Characteristics of Brightness [T_a=25°C]

Type	Viewing Half Angle	Radiant Intensity I _F =50mA unit: mW/sr			Outer Dimension	
		Minimum	Typical	Maximum	Dimension	Figure
L890-01AU	±10°		60		f 5	1
L890-02AU	±5°		70		f 5	2
L890-03AU	±15°		50		f 5	3
L890-04AU	±20°		30		f 5	4
L890-05AU	±40°		8		f 5	5
L890-06AU	±6°		80		f 5	6
L890-09AU	±25°(Long)		50		f 5	7
	±15°(Short)				Oval	
L890-33AU	±15°		20		f 3	9
L890-36AU	±30°		15		f 3	10

‡ Radiant Intensity is measured by Tektronix J-16.

‡ Total Radiated Power is measured by Photodyne #500.