

L760/850-04A Bi-Color LED for medical analysis

Bi-color LED of L760/850-04A consists of DDH structure AlGaAs LEDs mounted on a lead frame with a clear epoxy lens.

On forward bias it emits a band of visible light, which peaks 760nm and 850nm at anode common.


Features

- 1) High Reliability
- 2) High Power
- 3) Anode Common

Specifications

- 1) Product Name Bi-color LED
- 2) Type No. L760/850-04A
- 3) Chip
 - (1) Chip Material AlGaAs (DDH structure)
 - (2) Peak Wavelength 760nm and 850nm typ.
- 4) Package
 - (1) Type f5mm clear molding
 - (2) Resin Material Epoxy Resin
 - (3) Lead Frame Soldered

Outer dimension (Unit: mm)



Absolute Maximum Ratings

Item	Symbol	Maximum Rated Value		Unit	Ambient Temperature
		760nm	850nm		
Power Dissipation	PD	200	160	mW	Ta=25°C
Forward Current	IF	100		mA	Ta=25°C
Reverse Voltage	IR	10		V	Ta=25°C
Operating Temperature	TOPR	-30 ~ +85		°C	
Storage Temperature	TSTG	-30 ~ +100		°C	
Soldering Temperature	TSOL	260		°C	

‡ Soldering condition: Soldering condition must be completed within 3 seconds at 260°C

Electro-Optical Characteristics [Ta=25°C]

Item	Symbol	Condition	Minimum		Typical		Maximum		Unit
			760nm	850nm	760nm	850nm	760nm	850nm	
Forward Voltage	VF	IF=50mA			1.85	1.55	2.00	1.70	V
Reverse Current	IR	VR=5V					10		uA
Total Radiated Power	PO	IF=50mA	8.0	12.0	15.0	18.0			mW
Peak Wavelength	λP	IF=50mA	740	830	760	850	780	870	nm
Half Width	Δλ	IF=50mA			30	35			nm
Viewing Half Angle	Q1/2	IF=50mA			±20				deg.

‡ Total Radiated Power is measured by Photodyne #500

‡ Radiant Intensity is measured by Tektronix J-6512

EPITEX INC. : 4, Nishiaketa-Cho, Higashi-Kujyou, Minami-Ku, Kyoto, Japan

Tel.: ++81-75-682-2338 Fax: ++81-75-682-2267

e-mail: sales-dep@epitex.com

<http://www.epitex.com>